

Functions

ANSI A156.2 Series 4000 Grade 2

Non-Keyed Functions

SCHLAGE ANSI

AL10S F75 Passage Latch
Both levers always unlocked.



AL25D Exit Lock
Blank plate outside. Inside lever always unlocked. Specify door thickness, 1 3/8" (35 mm) or 1 3/4" (44 mm).



AL40S F76 Bath/Bedroom Privacy Lock
Push-button locking. Can be opened from outside with small screwdriver. Turning inside lever or closing door releases button.



AL44S Hospital Privacy Lock
Push-button locking. Unlocked from outside by turning emergency turn button. Turning inside lever or closing door releases button.



AL170 Single Dummy Trim
Single dummy trim for one side of door. Used for door pull or as matching inactive trim.



Keyed Functions

SCHLAGE ANSI

AL50PD F82 Entrance/Office Lock
Push-button locking. Push-button locks outside lever until unlocked with key or by rotating inside lever.



AL53PD F109 Entrance Lock
Turn/push-button locking: pushing and turning button locks outside lever requiring use of key until button is manually unlocked. Push-button locking: pushing button locks outside lever until unlocked by key or by turning inside lever.



AL70PD F84 Classroom Lock
Outside lever locked and unlocked by key. Inside lever always unlocked.




AL80PD F86 Storeroom Lock
Outside lever fixed. Entrance by key only. Inside lever always unlocked.



AL85PD F93 Hotel/Motel Lock
Outside lever fixed. Entrance by key only. Push-button in inside lever activates visual occupancy indicator, allowing only emergency masterkey to operate. Rotating inside lever or closing door releases visual occupancy indicator. Rotation of inside spanner button provides lockout feature by keeping indicator thrown.



 This icon designates functions available with interchangeable core options.